



WB100 (WB-124) or WB200

www.aivaka.com

Wireless Bridge WB-200 & WB-100/WB-124 @ A Glance

	WB-200	WB-100 (WB-124)	Comments
Range (Distance)	Over 2600-ft	Over 2600-ft	Measured line of sight
Valve Compatibility	DC Valves	24V AC Valves	
Controller Compatibility	Any 24V-AC Controller	Any 24V-AC Controller	
Night Operation	Continuous	3 Hours (24Hours)	
Daytime Operation	Continuous	Continuous	In direct Sunlight
Time To Charge Battery	5 Hours	5 Hours (16 Hours)	Full charge in direct Sunlight
Frequency	915MHz	915MHz	FCC certified ID: 2AKREMOD100915
Programming	Not Needed	Not Needed	Plug & Play
Default Valve Position	Last Position	Shut Off	
Battery Replacement	Not Needed	Not Needed	Over 5 Years
Tx Size (Clock Box)	2.6" x 2.6" x 1.6"	2.6" x 2.6" x 1.6"	Boxes are UL certified for outdoor/indoor use
Rx Size (Valve Box)	4.7" x 3.5" x 2.4"	4.7" x 3.5" x 2.4" (7.1" x 4.7" x 2.4")	Boxes are UL certified for outdoor/indoor use